

## TECHNISCHE SPEZIFIKATIONEN TYP 4000 (INNENVERZÄHNUNG)

| Zeichnungsnummer              | Dz<br>(mm) | Dn<br>(mm) | H<br>(mm) | Lz<br>(mm) | Ln<br>(mm) | n  | B<br>(mm) | M<br>(mm) | O<br>(mm) | U<br>(mm) | H1<br>(mm) | H2<br>(mm) | Hu<br>(mm) | Ho<br>(mm) | d<br>(mm) | m<br>(mm) | z   | x.m<br>(mm) | b<br>(mm) | T<br>(kg) |
|-------------------------------|------------|------------|-----------|------------|------------|----|-----------|-----------|-----------|-----------|------------|------------|------------|------------|-----------|-----------|-----|-------------|-----------|-----------|
| <b>4802.20.22.0-0.0625.00</b> | 705        | 504        | 92        | 675        | 575        | 32 | 18        | 16        | 627       | 623       | 83         | 83         | 9          | 9          | 520       | 8         | 65  | 0           | 83        | 95        |
| <b>4804.20.22.0-0.0897.00</b> | 973        | 786        | 97        | 944        | 850        | 36 | 18        | 16        | 899       | 895       | 88         | 88         | 9          | 9          | 800       | 8         | 100 | 0           | 88        | 141       |
| <b>4806.20.22.0-0.1087.00</b> | 1172       | 962        | 97        | 1134       | 1040       | 36 | 18        | 16        | 1089      | 1085      | 88         | 88         | 9          | 9          | 980       | 10        | 98  | 0           | 88        | 193       |
| <b>4808.20.25.0-0.1100.00</b> | 1200       | 963,5      | 110       | 1160       | 1040       | 36 | 22        | 20        | 1102      | 1098      | 96         | 96         | 14         | 14         | 980       | 10        | 98  | 0           | 96        | 239       |
| <b>4810.20.30.0-0.1220.00</b> | 1345       | 1061,6     | 108       | 1290       | 1150       | 40 | 22        | 20        | 1222      | 1218      | 98         | 98         | 10         | 10         | 1080      | 10        | 108 | 0           | 98        | 331       |
| <b>4812.20.30.0-0.1347.00</b> | 1470       | 1183       | 108       | 1425       | 1270       | 40 | 22        | 22        | 1350      | 1344      | 98         | 98         | 10         | 10         | 1200      | 10        | 120 | 0           | 98        | 371       |
| <b>4814.20.30.0-0.1385.00</b> | 1530       | 1186       | 144       | 1480       | 1290       | 48 | 26        | 24        | 1388      | 1382      | 134        | 134        | 10         | 10         | 1200      | 10        | 120 | 0           | 134       | 612       |
| <b>4816.20.30.0-0.1615.00</b> | 1750       | 1418,4     | 120       | 1705       | 1525       | 40 | 26        | 24        | 1618      | 1612      | 110        | 105        | 10         | 15         | 1200      | 12        | 120 | 0           | 110       | 572       |
| <b>4818.20.30.0-0.2003.00</b> | 2178       | 1776       | 144       | 2108       | 1898       | 72 | 30        | 27        | 2005      | 2000      | 134        | 134        | 10         | 10         | 1800      | 12        | 150 | 0           | 134       | 1062      |

